



RTH3100C For Heat Pump Systems

RTH3100C For Heat Pump Systems

QUALITY TEMPERATURE
CONTROL FOR HEAT PUMPS



KEY FEATURES

- Easy to install and use
- Emergency and auxiliary heat +/- indication
- Accurate temperature control of +/- 1° F for consistent comfort
- Mercury free
- Backlit display. Easy to see and read.
- Simplified operation

SPECIFICATIONS:

MODEL	RTH3100C
-------	----------

Master Carton

Qty	6
Dim. WxHxD (in.)	7.25 x 19 x 9.25
Carton Wt. (lbs.)	4.0
Cu. Ft	.74

Retail Package

Qty	1
Dim. WxHxD (in.)	7 x 9 x 2.25
Unit Wt. (lbs.)	.55
Cu. Ft	.08

Compatibility Chart

	RTH3100
Single Stage Heating and Cooling	No
Multistage Heating and Cooling	No
Heat Pump without Auxiliary Heat	No
Heat Pump with Auxiliary Heat	Yes
Gas Fireplace (24 Volt)	No
Electric Baseboard Heat (120-240 Volts)	No
Central Air Conditioning	No
Heating Only	No
Cooling Only	No
Hot Water	No
Steam or Gravity	No
750 Millivolt	No
Furnace (Warm Air)	No

UNITED STATES



CANADA



Automation and Control Solutions

Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422-3992
800-468-1502
yourhome.honeywell.com

67-5152
October 2005
© 2005 Honeywell International Inc.

Honeywell